



T31 Smart Plug








Your smart charge guard that saves energy

Supports a current of up to 16 A¹



Features

-  Visible Power Consumption
-  Remote Control via EZVIZ App
-  Energy-Saving Design
-  Timer & Schedule
-  Supports 2.4 GHz Wi-Fi
-  Overcharge Protection
-  Overload Protection

1 The T31 supports a maximum current of 16 A. To ensure safe operation, it is recommended to use appliances with a power rating of less than 3680 W.

Mechanical Specification

Material	PC V0
Flame Retardance	750°C fire-retardance
Ingress Protection (IP)	No

Electrical Specification

Power	16 A / 3680 W
Input Voltage	AC 85 V ~ 265 V
Frequency	50 / 60Hz
USB Output USBL	No
Max. Load (NC)	N / A
Max. Load (NO)	16 A / 3680 W
Wi-Fi Standard	802.11 b/g/n, 2.4 GHz (only)
Operating Temperature	-20°C ~ 40°C (-4.0°F ~ 104.0°F)
Storage Temperature	-20°C ~ 40°C (-4.0°F ~ 104.0°F)
Max Humidity	80%

Protection

Overload Protection	Supports
Lightning Protection	Supports
Overcurrent Protection	Supports
Fuse for Power Supply	Supports
Fuse for Output Circuit	No
Surge Protection	Supports
Child Safety Shutter Protection	Supports

Smart Features

Third-Party Compatibility	Matter
Power Counting	Supports
Customized Maximum Power Limit	Supports

In the box

- Smart Plug
- Regulatory Information
- Quick Start Guide

Certifications

CE (RED, LVD, ROHS, EMC) / REACH / SVHC

Specifications are subject to change without notice. "🌈", "EZVIZ" and other trademarks and logos are the properties of EZVIZ in various jurisdictions.