



# *Alarm Light*

---

Active alerts. Enhanced protection.

*Works with EZVIZ Smart Home  
Gate Opener<sup>1</sup>*



## Key Features

- **Siren & Strobe Warning:** During gate operation (opening/closing), the alarm light outputs an audible siren and high-intensity strobe flashes to provide a clear visual and sound warning, improving awareness and operational safety.
- **2-Wire Installation:** Uses a simplified 2-wire connection for fast wiring and clean integration between the alarm light and the gate opener, reducing installation complexity compared with multi-wire or legacy setups.
- **Easy Control in the EZVIZ App:** Supports brightness adjustment via the EZVIZ App, allowing the alarm light output level to be configured based on site conditions and user preference.
- **Weatherproof Design:** Weather-resistant housing supports continuous outdoor operation and reliable performance under typical environmental exposure (e.g., rain, wind, and temperature changes).

## Stand-out alerts, 24/7

The instant your gate starts moving, the alarm light springs into action with a bold strobe flash and a powerful siren—so everyone nearby gets the message right away. It's a simple, high-impact way to boost safety and add extra protection at your entrance.



## Fast and easy setup, ready for every scenario

With a simple 2-wire connection, the alarm light links to your gate opener in minutes—no complicated wiring, extra labor, or surprise costs. Two mounting options give you the freedom to position it where it works best for your entrance and security needs.



Hassle-Free 2-Wire Installation



Dual set-up modes to meet different needs

Top Mount



Wall Mount



1 Please note that this alarm light is compatible with all current EZVIZ smart gate openers, with the exception of the HG2 600. Compatibility may expand as EZVIZ introduces new devices. Please verify product compatibility with your specific model prior to purchase.

# Specifications CS-HGL2-R100-L

## Alarm Light


Connection Method	Wired connection with gate opener (2-wire), digital signal transmission
Operation Conditions	-30°C to 55°C , humidity 95% or less (non-condensing)
Protection Rating	IP55
Size (Without Package)	90 × 90 × 139 mm
Size (With Package)	125 × 125 × 164 mm
Weight (Without Package)	263 g
Weight (With Package)	525 g

## In the box

- Alarm Light
- Wall Bracket
- Drill Template
- Screw Kit × 2
- Regulatory Information
- Quick Start Guide

## Certifications

CE / REACH / WEEE / RoHS

Specifications are subject to change without notice. "  ", "EZVIZ" and other trademarks and logos are the properties of EZVIZ in various jurisdictions.