

C2C 720p

## Simple but Powerful

An HD 720p Wi-Fi camera with a magnetic base, designed for simple and quick installation.

## **Key Features**



720p



Supports MicroSD card slot, up to 256GB



Supports 2.4GHz Wi-Fi (IEEE802.11b, 802.11g, 802.11n)



Two-way audio




True Day/Night camera with auto-switching. Infrared night vision up to 10 meters.



# Easy installation

The C2C comes with a magnetic base and mounting kitfor easy placement on walls or ceilings. Once set up, you can manually adjust it to cover just about any angle you need.



The C2C delivers HD 720p video and extensive coverage with a 101° wide-angle lens, so you can keep an eye on what's valuable to you.





## Keep them safe, day and night

When it's dark, the C2C automatically switches to nightvision mode for around-the-clock HD video coverage, ensuring a night vision up to 10 meters.



# Instant alerts (manual activation required)

The C2C watches for movement. It will take a picture and send alerts to your smartphone when it detects motions.



## Two-way audio

The camera comes with a built-in microphone and speaker, enabling two-way audio via the camera and your phone or tablet.





# Specifications Model CS-CV206-E0-1D1WF

#### Camera

Image Sensor 1/4" 1MP HD Progressive Scan CMOS

Shutter Speed Self-adaptive shutter

Lens 2.8 mm @F2.5, View Angle: 86°, Diagonal

View Angle: 101°

Lens Mount M12

Day & Night IR-cut filter with auto-switching

DNR 3D DNR

WDR Digital WDR

#### Compression

Video Compression H.264

H.264 Type Main Profile

Video Bit Rate HD; Standard. Adaptive bit rate.

#### Image

Max. Resolution 1280×720

Image Settings Brightness, contrast, saturation, etc.

(configurable via EZVIZ Studio)

BLC Support

#### Network

Storage Supports MicroSD card (max. 256GB)

Smart Alarm Motion detection

Wi-Fi Pairing SmartConfig (Wi-Fi One-Key Configuration)/AP paring

Protocol EZVIZ Cloud proprietary protocol

Interface Protocol EZVIZ Cloud proprietary protocol

General Features Anti-Flicker, Dual-Stream, Heartbeat Messages, Mirror

Image, Password Protection, Watermark

Minimum Network

Requirements

1Mbps

#### Wi-Fi

Standard IEEE802.11b, 802.11g, 802.11n

Frequency Range 2.4 GHz ~ 2.4835 GHz

Channel Bandwidth Supports 20MHz

Security 64/128-bit WEP, WPA/WPA2, WPA-PSK/WPA2-PSK

Transmission Rate 11b: 11Mbps, 11g: 54Mbps, 11n: 72Mbps

#### General

Operating Conditions  $-10^{\circ}\text{C} \sim 50^{\circ}\text{C} (14^{\circ}\text{F} \sim 122^{\circ}\text{F})$ , Humidity 95%

or less (non-condensing)

Power Supply DC 5V±10%

Power Consumption MAX. 4.0 W

IR Range MAX. 10 meters

Product Dimensions 110 x 58 x 38 mm (4.33 x 2.28 x 1.50 inch)

Packaging Dimensions 149 x 91.5 x 87.5 mm (5.87 x 3.60 x 3.44 inch)

Weight 100 g (3.53 oz)

## Package Contents:

- C2C
- 3 Meters USB Cable
- Power Adapter
- Foam Sticker
- Metal Plate (3.5mm Hole Diameter)
- Quick Start Guide

### Certificates

FCC/UL/CE/RoHS/WEEE/REACH