



C4S

Vandal-Proof Design, Strong and Reliable

A Full HD 1080p Wi-Fi camera protected against all types of weather and vandalism.

Key Features

Full HD

1080p

Smart 264

Adaptive Streaming Technology



Supports 2.4GHz Wi-Fi



True Day/Night camera with auto-switching. Infrared night vision up to 30 meters.



IP66 Dustproof and Waterproof

PoE

PoE/Wi-Fi optional



Supports MicroSD card slot, up to 128GB



Secure cloud recording* (optional)




IK10 vandal-proof

With its vandal-proof design, the C4S is strong and durable.



Optional Wi-Fi and PoE connectivity

Easily set up the C4S by connecting and powering it with the same Ethernet cord.



Full HD 1080p video

Take pictures and record real-time video in Full HD 1080p.



120dB WDR

See every detail in the best lighting with WDR, which automatically balances white levels for clearer video and images.




Night vision

The C4S delivers clear-as-day night vision up to 30 meters.



Instant alerts (manual activation required)

The C4S watches for movement. It will take a picture and send alerts to your smartphone when it detects motions.



Specifications

Model CS-C4S-52(W) EFR (4mm) 2.0 MP 1/2.7" CMOS Ceiling IP Camera

Camera

Image Sensor	1/3" Progressive Scan CMOS
Minimum Illumination	0.02 lux @(F2.0, AGC ON), 0 lux with IR
Shutter Speed	Self-adaptive shutter
Lens	4mm@ F2.0, Angle of view: 90°, opposite angle 107.5°
Lens Mount	M12
Day & Night	IR-cut filter
DNR	3D DNR
WDR	Digital WDR

Compression

Video Compression	H.264
H.264 Type	Main Profile
Video Bit Rate	HD, Balance and Smooth.

Compression

Communication Interface	1 RJ45 10M/100M self-adaptive Ethernet port
-------------------------	---

Image

Max. Resolution	1920×1080
Image Settings	Brightness, contrast, saturation, etc. (configurable via EZVIZ Studio)
BLC	Support

Network

Storage	Supports MicroSD card (max. 128GB)
Smart Alarm	Motion Detection
Wi-Fi Pairing	SmartConfig (Wi-Fi One-Key Configuration)
Protocol	EZVIZ Cloud proprietary protocol
Interface Protocol	EZVIZ Cloud proprietary protocol
General Features	Anti-Flicker, Dual-Stream, Heartbeat Messages, Mirror Image, Password Protection, Watermark
Minimum Network Requirements	2Mbps

Wireless Specifications (for Wi-Fi-supported devices)

Standard	IEEE802.11b, 802.11g, 802.11n
Frequency Range	2.4 GHz ~ 2.4835 GHz
Channel Bandwidth	Supports 20MHz
Security	64/128-bit WEP, WPA/WPA2, WPA-PSK/WPA2-PSK, WPS
Transmission Rate	11b: 11Mbps, 11g: 54Mbps, 11n: 135Mbps

General

Power Supply	DC 12V±10%
Power Consumption	6W MAX (ICR 9W)
IP Grade	IP66
IR Range	MAX. 30 meters
Product Dimensions	116.2mm x 82mm
Packaging Dimensions	195 x 140 x 98mm
Weight	300g

Package Contents:

- C4S X 1
- Power Adapter with 1.5 Meters Power Cable (Optional) X 1
- Screw Kit X 1
- Allen Wrench X 1
- Mounting Template X 1
- Quick Start Guide X 1

Requirements

- Operating Conditions: -30°C ~ 60°C, Humidity 95% or less (non-condensing)

Certificates

FCC/UL/IC/NOM/CE/RoHS/WEEE/REACH

Specifications are subject to change without notice. EZVIZ is a registered trademark of Hangzhou EZVIZ Network Co., Ltd.
Other brands and product names are trademarks or registered trademarks of their respective holders.

<https://www.ezvizlife.com/>